

freedom

TILE PERFORMANCE DATA

COLORED BODY PORCELAIN TILE - Rectified Monocaliber

PHYSICAL PROPERTIES	TEST ASTM	NORTH AMERICAN STANDARD A137.1*	RESULTS
Water absorption *	C373	≤ 0.5%	COMPLY WITH ANSI A137.1
DCOF Average dynamic coefficient of friction **	BOT 3000 test	≥ 0.42	≥ 0.42
Resistance to freeze/thaw cycling *	C1026	As reported	RESISTANT
Warpage (edge)	C485	Warpage ± 0.4% or ± 0.05 in	COMPLY WITH ANSI A137.1
Warpage (diagonal)	C485	Warpage ± 0.4% or ± 0.07 in	COMPLY WITH ANSI A137.1
Wedging	C502	± 0.25% or ± 0.03 in	COMPLY WITH ANSI A137.1
Chemical resistance	C650	As reported	UNAFFECTED
Breaking strength	C648	250 lbf or greater	COMPLY WITH ANSI A137.1
Thickness	C499	Range: 0.04 in	COMPLY WITH ANSI A137.1

- Average values referred to our production and related to the matt finish of the product.
- ** As far as values relating to the matt finish of the product and to tests carried out by certified external laboratories whose results are availble upon request at Headoffice, we are willing to check the lot you are interested in purchasing.
- Be sure to use tiles belonging to the same caliber.
- Landmark tiles can be slippery when wet. We recommend to make sure that the surface is always dry.
- The information provided can be subject to change. Please refer to Icusa.com for the latest, most accurate and up-to-date information.























freedom

Freedom is the porcelain ceramic collection for floors and walls that reflects genuine slate in a contemporary way, created for spaces that express an immense tie with nature and with traditional American architecture. Color versatility and magnetic charm make any surface a work of art, unique and unrepeatable. Sizes, colors and decors enrich the creativity of interior designer to create amazing venues.

www.lcusa.com



SIZES 24"x24" / 12"x24" / 4"x24" / 12"x12" / 6"x12"

COLORED BODY PORCELAIN TILE - Rectified Monocaliber



Color Shading

INDIAN SUMMER



Color Shading


BRAZILIAN BLOOMY



Available sizes

12"x24" 4"x24" *0.35" *0.35"

Available sizes



2"x2" 2"x6" 12"x12" 12"x12" 6"x12" ±0.35" ±0.35" ±0.35"

Available sizes



12"x12" 12"x12" 6"x12" *0.35" *0.35" *0.35"

The color of tiles printed in this catalog may differ from actual tiles. Tile color reproductions in this catalog are representative only. Slight tone and shade variations are inherent in porcelain tiles. Before selecting a color, we recommend that you contact your local representative, who will provide you with a sample piece of the requested tile.

This porcelain tile product is manufactured with a V3 shade variation. Remember that the amount of color as well as the texture of each piece may vary from tile to tile. Inspect the product immediately upon delivery and select tiles from many boxes during installation to minimize and blend any possible color difference.










\$10% MULTICOLOR GOLD Color Shading

MULTICOLOR DARK



Color Shading





12"x12" 12"x12" 6"x12" *0.35" *0.35" *0.35"

Ice Winter







Mosaic C 2"x6" 12"x12"



Mosaic C 2"x6"







Mosaic C 2"x6"



Mosaic C 2"x6" 12"x12"

Mosaic A 2"x2"

DECOR RANGE





Ice Winter

Mosaic C 2"x6"







Indian Summer Wall
6"x12"

Brazilian Bloomy Wall
6"x12"

Multicolor Gold Wall
6"x12"

Multicolor Dark Wall
6"x12"



TRIM TILES

	COVE BASE	BULLNOSE
	6″x12″	3″x24″
CE WINTER	•	•
NDIAN SUMMER	•	•
MULTICOLOR GOLD	•	•
BRAZILIAN BLOOMY	•	•
MULTICOLOR DARK	•	•

INFORMATION

RECOMMENDED USE

Freedom is recommended for indoor walls and floors and outdoor walls in residential and commercial applications. We recommend Freedom for interior and outdoor walls and floors (20 mm only) as well as for exterior flooring. Landmark recommends an offset no greater than 30%, if a staggered pattern is required for tiles of 20 inches or longer. Visit Icusa.com for detailed instructions of installation.

Do not apply any wax or sealer to the product after installation. Regular cleaning is the best way to keep Freedom tiles looking good. Use clean, hot water (add household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. Please visit Icusa.com. For further information regarding the care and maintenance of Landmark products.

Landmark guarantees that its products will meet or exceed the performance specifications set out in ANSI A137.1- 2012 and in the performance specifications section of the Landmark general catalog. For more information, please visit our website at Icusa.com.